

*It's stronger
It's Faster
It's Economical
It just works works & works...
Without tiring*

Smart - Ex Weigh Filler

The Machine Is Best for...
Extruded Snacks Like Kurkure & Potato
Chips, Farsan, Chiwda, Namkeen,
Dry - Fruits, Pulses, Grains, Tea, Sugar,
Seeds etc.

Smart Ex weigh Filler
(Available with Single head, 2 Heads,
3 Heads, 4 Heads)

This model is specially designed for
packaging of material having uneven
volume & density like potato chips,
snacks, Kurkure, dry fruits, grains,
pulses, tea, sugar, seeds etc. It is based
on load cell electronic weighing
technology which measures the material
with high precision before being packed
into pouches. The machine capacity
ranges from 5 g. to 500 g. pouch weight.
It has PLC control, making it intelligent &
smart. Mechanical functions are
pneumatically operated. It is low in
maintenance, user friendly with option of
single & multiple heads depending upon
customer's requirement.

Additional systems available to all our packaging machine

- B Online batch coding device
- B Inert gas flushing systems
- B 3 Side, 4 Side & Center Sealing
- B Batch Cutting device
- B 'No material' machine stop
- B Available in GMP Model for Pharmaceutical users.
- B Static charge eliminator for dust free sealing.



Smart - Ex Weigh Filler

Specifications	Filling Capacity (Range)	5gms to 500gms
	Filling Speed	600 to 2500 Pouches/hr
	Control	PLC Control
	Mode of Operation	Pneumatic
	Weighing Accuracy	+ 1 gm or Weight of 1 piece.
	Packaging Material	Laminated Films
	Machines Weight (Approximate)	450 kg
	Dimension (Approximate)	Width 1100 X Length 1500 X Height 2450
	Power Requirement	220V Single Phase OR 420V Three Phase
	Compressed Air Requirement	6 CFM with 6 bar pressure
Available in Variety of Models	5 g to 50 g, 10 g to 100 g, 20 g to 250 g, 50 g to 500 g	

(The design/ specification are subject to change without notice on account of continuous improvement in product quality.)

Special Features

- B PLC controlled machine with LCD display & tactile keyboard.
- B Built in self fault diagnosis Systems.
- B Password protection for settings.
- B Minimum maintenance.
- B If no material machine stops (optional).
- B Batch cutting device (optional).
- B Epoxy powder coated structure.
- B High Filling accuracy.
- B Weight adjustment through thump switch/keypad.
- All Contact parts SS 304 With mirror Finish.

